



P1:	M-Y139A
	M-139B
P2,P3:	M-Y139A
	M-139H
P4:	M-426E

Customer No: No.4

NOTE: All relevant materials are complied with RoHS directive .
LOGO ON DOUBLE SIDES OF OVERMOLD

1C29		
P2	P1	P3
1	1	1
2	2	
3	3	
4	4	4
5	5	5
6	6	6
7	7	2
8	8	3
9	9	3
SHIELD	SHIELD	SHIELD

7&8	BLACK HEAT SHRINK TUBE $\phi 3.0 \times 22\text{mm}$	3	M743
	ALUMINUM FOIL 33*65mm	3	M579
	MOLDED PE COLOR TRANSPARENT		M280
	MOLDED PVC BLACK		M304
6	UL2464 7C 28AWG, ALUM-MYLAR FOIL SHIELDING WITH DRAIN WIRE, OD 5.0mm, JACKET BLACK, DRAWING No. EMAL2607C-142	250mm	M304
5	UL2464 9C 28AWG, ALUM-MYLAR FOIL SHIELDING WITH DRAIN WIRE, OD 5.0mm, JACKET BLACK, DRAWING No. EMAL2609C-002	250mm	M304
4	HEX-NUT 4.75*8.5mm, #4-40	4	M95
3	MOLDED THUMBSCREW #4-40, LENGTH 46.5mm, BLACK	2	M95
2	DB9 MALE, GOLD FLASH ON CONTACTS, BLUE INSULATOR	2	M108
1	DB9 FEMALE, GOLD FLASH ON CONTACTS, BLUE INSULATOR	1	M108

No.	DESCRIPTION	QTY	Supplier
APPROVED			
CHECKED	HU		
DRAWING	XIE		
DATE	30/MAR/10	ITEM NO.	1C29
		UNIT	mm

Cable Length	Other Spec.
0 ~ 200mm	+10mm
201 ~ 1000mm	+20mm
1001 ~ 1500mm	+25mm
1501 ~ 2100mm	+30mm
2100mm	+40mm

© LOCKED